(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



1 (FFT) FTT(1871) (1 GTG) FT 1871 GTG) FTC(1871 GTG) FTC(1871 GTG) FTC(1871 GTG) FTC(1871 GTG) FTC(1871 GTG)

(43) International Publication Date 5 February 2004 (05.02.2004)

PCT

(10) International Publication Number WO 2004/011411 A1

(51) International Patent Classification7: 51/16, 51/255, 63/307

C07C 51/265,

(21) International Application Number:

PCT/KR2003/000023

(22) International Filing Date: 7 January 2003 (07.01.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 10-2002-0044946

> Injection of Reactant

30 July 2002 (30.07.2002)

(71) Applicant (for all designated States except US): SK CHEMICALS CO., LTD. [KR/KR]; 600, Jeongja-1dong, Jangan-gu, Suwon, Gyeongii 440-301 (KR).

- (72) Inventors; and
- (75) Inventors/Applicants (for US only): ROH, Hang-Duk [KR/KR]; 106-204, Sangrok-maeul, 1514 Sa-dong, Ansan, Gyeonggi 425-170 (KR). LEE, Jong-In [KR/KR]; 1001-802, Kunyoung Aptartment, 222, Gumi-dong, Bundang-gu, Songnam, Gyeonggi 463-802 (KR). SHIM, Hyun-Sup [KR/KR]; 501-203, Samhogarden Aptartment, Banpo-dong, Seocho-gu, Seoul 137-040 (KR). KIM. Byung-Hui [KR/KR]; 101-201, Jugong Aptartment, 855, Jowon-dong, Jangan-gu, Suwon, Gyeonggi 440-200 (KR). CHO, Jun-Sang [KR/KR]; 425-2002, Byucksan Aptartment, Yeonkkoch-maeul, Jeongia-1dong, Jangan-gu, Suwon, Gyeonggi 440-301 (KR). LEE, Yoon-Seo [KR/KR]; 723-202, Youngpoong Aptartment, Cheoncheon-dong, Jangan-gu, Suwon, Gyeonggi 440-330 (KR).
- (74) Agent: CHUNG-UN PATENT & LAW FIRM; 2nd Fl., Changsang Bldg., 1543-12, Seocho 3-dong, Seocho-gu, Seoul 137-872 (KR).

[Continued on next page]

(54) Title: METHOD OF PRODUCING TRIMELLITIC ACID Condenser Gas Treatment Nitrogen and Analysis Oxidizing Reactor Reservoir Reservoir Vessel 2 Vessel 1 Air Compressor Storage and

(57) Abstract: Disclosed is a method of producing trimellitic acid through the liquid-phase oxidation of pseudocumene in acetic acid. The oxidation comprises a) conducting a first oxidation using an initial oxidizing catalytic system at 120-200;É for 5-20 min in an oxidizing reactor, said initial oxidizing catalytic system comprising at least three compounds selected from the group consisting of cobalt compound, manganese compound, zirconium compound and bromine compound: b) conducting a second oxidation in situ at 160-220 É for 30-60 min under addition of an additional catalytic system, said additional catalytic system comprising at least two compounds selected from the group consisting of cobalt compound, manganese compound, zirconium compound, and bromine compound; and c) completing the oxidation of pseudocumene at a temperature from 180 to 230; É for a time from 5 to 20 min without the addition of catalysts into the reactor. The pressure is adjusted in the range from 100 to 450 psig over the steps a), b) and c).